

电磁阀 /Solenoid Valve




型号注释 /Note for type:

<b>PU</b>	<b>220</b>	—	<b>15</b>	—	<b>AC110V</b>	—	<b>E</b>
↓	↓		↓		↓		↓
系 列/Series: PU: 二位二口电磁阀 PU: 2 postion 2 way Solenoid Valve	动作方式: Acting type: 220:直动式 220: Directly operated		接管口径: Port size: 15:G1/2" 20:G3/4" 25:G1" 35:G1 1/4" 40:G1 1/2" 50:G2"		线圈电压: Coil voltage: DC12V DC24V AC24V 50/60Hz AC110V 50/60Hz AC220V 50/60Hz AC380V 50/60Hz		油封代号: Oil seal symbol: Blank(空白): NBR E:EPDM V:VITON

技术参数 /Specification:

型 号/Type	PU220-06	PU220-08	PU220-10	PU220-15	PU220-20	PU220-25
工作介质 /Fluid	压缩空气、水、油 /Compressed Air、Water、Oil					
动作方式 /Acting type	直动式 /Directly operated					
型式 /Type	常闭式 /Normally closed					
接管口径 /Port size (G)	1/8"	1/4"	3/8"	1/2"	3/4"	1"
工作压力范围 /Operating pressure range (Mpa)	0-0.8					
使用温度范围 /Ambient temperature (°C)	-5-60					

外形尺寸 /Dimension(mm):



符号 /symbol 型号 /type	A	B	C	K
PU220-06	22	72	22	G1/8"
PU220-08	35	75.5	25.4	G1/4"
PU220-10	55	79.5	30	G3/8"
PU220-15	66.5	101	48	G1/2"
PU220-20	71	107	48	G3/4"
PU220-25	96	120	70	G1"

